

BOLT-SLIM-120

Slim 1200mm LED Batten



Description

The BOLT-SLIM LED Batten Series is an ideal modern replacement for traditional T8 and T5 fluorescent battens. Featuring a “quick fix” design, which ensures a hassle-free installation process. This batten comes with a quad wattage option, allowing users to toggle between 20W (600mm) and 40W (1200mm) settings to adjust brightness according to desired light level required. The switch for this adjustment is conveniently located on the LED driver.

Constructed from high-quality pressed sheet metal and finished with a white powder coat, complimented with a high transparency opal polycarbonate diffuser. The BOLT-SLIM Series is available in both 1200mm and 600mm lengths, making it versatile for various settings. Tricolour switchable, allowing the colour temperature output of the LED batten to be changed with a dip switch on the internal driver located inside the fitting. LED Colour temperatures - Warm White 3000K/Neutral White 4000K/White 5700K. Non-dimmable. Suitable for domestic applications such as laundries, garages, and storerooms, as well as commercial environments like underground car parks.



Specification Features

- Input Voltage: 240V AC
- Power (W): 20W/25W/35W/40W
- IP rating (IP): IP44
- Lumens (lm):

(20W) Warm White 3000K - 2870lm

(25W) Warm White 3000K - 3580lm

(35W) Warm White 3000K - 4725lm

(40W) Warm White 3000K - 5445lm

(20W) Neutral White 4000K - 3020lm

(25W) Neutral White 4000K - 3830lm

(35W) Neutral White 4000K - 5130lm

(40W) Neutral White 4000K - 5830lm

(20W) White 5700K - 3015lm

(25W) White 5700K - 3795lm

(35W) White 5700K - 5005lm

(40W) White 5700K - 5625lm
- LED type: SMD
- CCT: 3000K - 4000K - 5700K
- CRI: ≥80
- Beam angle (°): 120°
- Dimmable: No
- Lifespan (hrs): 50,000hrs
- Installation: Surface Mounted or Suspended



Diagrams / Additional

Item No.	Variant	CCT
BOLT-SLIM-120	66140	TRIO

